

Outlet (basic) [type F]

Wall outlet with grounding

<p>Components</p> <p>Outlet (basic) [type F] is a prefabricated device. All parts are purchased separately.</p>	<p>Core</p> <p>OutletCore (basic) [type F] OutletCore (basic) vertical [type F]</p> <p>Covers</p> <p>All covers consist of two elements of the same color: the front panel and the receptacle cap.</p> <p>SoloCover (basic) [type F] It is used when the outlet is installed as a separate device.</p> <p>SideCover (basic) [type F] It is used when the outlet is installed on the right or left (top or bottom) of the device set.</p> <p>CenterCover (basic) [type F] It is used when the outlet is installed between the device set.</p> <p>Frames</p> <p>Frames for two, three, four, and five Ajax outlets and switches in any combination*.</p> <ul style="list-style-type: none"> • Frame (2 seats) • Frame (2 seats) vertical • Frame (3 seats) • Frame (3 seats) vertical • Frame (4 seats) • Frame (4 seats) vertical • Frame (5 seats) • Frame (5 seats) vertical <p><i>* Combinations with smart outlets are available only in horizontal orientation.</i></p>
<p>Configuration</p>	<p>Single outlet</p> <p>Outlet (basic) [type F] is installed as a separate device.</p> <p>Combined outlet</p> <p>Outlet (basic) [type F] is combined as a set with Ajax outlets and/or LightSwitch switches and installed into Frame side by side.</p>
<p>Cover colors</p>	<p>Black</p> <p>White</p> <p>Fog</p> <p>Gray</p> <p>Graphite</p> <p>Ivory</p> <p>Oyster</p> <p>Olive</p>
<p>Recommendations</p>	<p>The device is designed for indoor use only. A professional electrician should install the device.</p>

Power supply	Power supply voltage 250 V~, 50/60 Hz Maximum load current 16 A Output power up to 3.6 kW (resistive load at 250 V~) Electric shock protection class Class I (with grounding terminal)
Operating parameters	Operating temperature range from –10 °C to +40 °C from 14 °F to 104 °F Operating humidity up to 75% with no condensation Protection class IP20

<p>Dimensions</p>	<p>OutletCore (basic) [type F] 77.3 × 74.2 × 32.8 mm 3.04" × 2.92" × 1.29"</p> <p>OutletCore (basic) vertical [type F] 74.2 × 74.5 × 32.8 mm 2.92" × 2.93" × 1.29"</p> <p>SoloCover (basic) [type F] front panel — 82.3 × 82.3 × 9.2 mm receptacle cap — 44 × 19.5 mm front panel — 3.24" × 3.24" × 0.36" receptacle cap — 1.73 × 0.77"</p> <p>SideCover (basic) [type F] front panel — 82 × 76.2 × 9.2 mm receptacle cap — 44 × 19.5 mm front panel — 3.23" × 3" × 0.36" receptacle cap — 1.73 × 0.77"</p> <p>CenterCover (basic) [type F] front panel — 82 × 70.5 × 9.2 mm receptacle cap — 44 × 19.5 mm front panel — 3.23" × 2.78" × 0.36" receptacle cap — 1.73 × 0.77"</p> <p>Frames</p> <p>Frame (2 seats) — 82.8 × 153.5 × 6.3 mm Frame (2 seats) vertical — 153.5 × 82.8 × 6.3 mm Frame (3 seats) — 82.8 × 224.5 × 6.3 mm Frame (3 seats) vertical — 224.5 × 82.8 × 6.3 mm Frame (4 seats) — 82.8 × 295.5 × 6.3 mm Frame (4 seats) vertical — 295.5 × 82.8 × 6.3 mm Frame (5 seats) — 82.8 × 366.5 × 6.3 mm Frame (5 seats) vertical — 366.5 × 82.8 × 6.3 mm</p> <p>Frame (2 seats) — 3.26" × 6.04" × 0.25" Frame (2 seats) vertical — 6.04" × 3.26" × 0.25" Frame (3 seats) — 3.26" × 8.84" × 0.25" Frame (3 seats) vertical — 8.84" × 3.26" × 0.25" Frame (4 seats) — 3.26" × 11.63" × 0.25" Frame (4 seats) vertical — 11.63" × 3.26" × 0.25" Frame (5 seats) — 3.26" × 14.43" × 0.25" Frame (5 seats) vertical — 14.43" × 3.26" × 0.25"</p>
--------------------------	--

Weight	<p>OutletCore (basic) [type F] 46 g 1.63 oz</p> <p>OutletCore (basic) vertical [type F] 46 g 1.63 oz</p> <p>SoloCover (basic) [type F] front panel — 12 g receptacle cap — 5 g front panel — 0.44 oz receptacle cap — 0.19 oz</p> <p>SideCover (basic) [type F] front panel — 12 g receptacle cap — 5 g front panel — 0.41 oz receptacle cap — 0.19 oz</p> <p>CenterCover (basic) [type F] front panel — 11 g receptacle cap — 5 g front panel — 0.38 oz receptacle cap — 0.19 oz</p> <p>Frames</p> <p>Frame (2 seats) — 16 g Frame (2 seats) vertical — 16 g Frame (3 seats) — 22 g Frame (3 seats) vertical — 22 g Frame (4 seats) — 28 g Frame (4 seats) vertical — 28 g Frame (5 seats) — 34 g Frame (5 seats) vertical — 34 g</p> <p>Frame (2 seats) — 0.57 oz Frame (2 seats) vertical — 0.57 oz Frame (3 seats) — 0.78 oz Frame (3 seats) vertical — 0.78 oz Frame (4 seats) — 1 oz Frame (4 seats) vertical — 1 oz Frame (5 seats) — 1.2 oz Frame (5 seats) vertical — 1.2 oz</p>
Complete set	Depends on the kit
Warranty	24 months