

For single-leaf doors up to size EN 4 (1,100 mm)

Product description

- Rack and pinion closer with link arm L190
- Certified in compliance with EN 1154, size 2-4
- Suitable for fire and smoke protection doors
- For single action doors up to 1100 mm wide

Overview of Advantages

- Can be used for left and right-handed doors
- Can be used with concealed mounting plate, suitable for fire and smoke protection doors
- Axis height adjustable up to 14 mm
- Closing speed, latching speed and backcheck adjustable via front facing regulating valves
- Thermodynamic valves for consistent performance
- Variable adjustable closing force
- Opening angle up to 180°
- Effective backcheck and latching speed range adjustable
- Large range of applications
- Standard colours: silver EV1; white, similar to RAL9016; brown, similar to RAL8014; black, similar to RAL9005
- Customised finishes available on request

Note

- Link arm must be ordered separately

Characteristics for hold open link arm L191


- Hold-open angle adjustable up to 150°
- Hold-open mode can be enabled and disabled as required
- Same installation as link arm
- Cannot be used with fire and smoke protection doors

The advantages at a glance

Customer segment	Advantages
Project planners	Extensive range of uses: Fire and smoke protection doors as well as standard doors Modern design Compact design Fulfills barrier-free building requirements Same dimensions and design with and without mounting plate
Builders	One drilling template overall Adjustable to nearly all door and frame types Quick and easy installation Quickly and easily adjustable Suitable for left and right handed doors, in both door and frame mounted applications
Trade	Reduced inventory costs due to modular product range One single product suitable for a large variety of mounting positions Complementary accessories available for the whole product range
User	Largely unaffected by temperature fluctuations because of thermodynamic valves Easier door opening and improved accessibility due to rapidly decreasing torque Backcheck feature offers optimum protection for doors and walls

Technical data

Closing force	EN 2-4
Door width up to	1.100 mm
Suitable for fire doors	Yes
DIN-direction	Left / right handed
Closing speed	Variable between 180°-15°
Latching speed	Variable between 15°-0°
Backcheck effect	Variable above 75°
Hold-open mode (with hold-open link arm L191)	Adjustable 75°-150°, can be enabled and disabled
CE marking for building products	Yes
Certified in compliance with	EN 1154
Length	223 mm
Height	60 mm
Depth	50 mm



ASSA ABLOY DC200

For single-leaf doors up to size EN 4 (1,100 mm)

Weight	1.6 kg
--------	--------

Variants that can be ordered

Order number	Description
DC200-----DEV1-	EN size 2-4, silver EV1
DC200-----D9016	EN size 2-4, white, similar to RAL9016
DC200-----D8014	EN size 2-4, brown, similar to RAL8014
DC200-----D9005	EN size 2-4, black, similar to RAL9005
DC200-----DXXXX	EN size 2-4, customised finish