

# G1016G

## 16-Port Gigabit Ethernet Switch



# G1016G

## 16-Port Gigabit Ethernet Switch

---

### Descriptions

G1016G is a 16-port gigabit Ethernet unmanaged switch independently designed by IP-COM. The switch supports wire-speed forwarding of all ports to ensure smooth transmission of large files and video streaming. It features a compact metal body, and supports desktop, wall and rack mounting. As a flexible and simple-to-use device, it can be connected to such network devices as computers and network cameras. It is your ideal choice for video surveillance and wired networking in such scenarios as SMBs, communities, factories, and schools.

## Key Feature

- Compliant with IEEE802.3, IEEE802.3u, IEEE802.3ab, IEEE802.3x
- 16 10/100/1000 Base-T Ethernet ports
- 8K MAC address and MAC address automatic learning
- IEEE 802.3x full-duplex flow control and half-duplex backpressure flow control
- Plug and play
- 32 Gbps non-blocking wire-speed forwarding backplane bandwidth
- 4 Mb large buffer design
- With 19-inch body design, and support desktop, wall and rack mounting

## Main Features



### With Rack Design

Standard 19-inch Device Designed for Rack.



### Mute and Energy Saving

Fanless Design Greatly Reduces Noise.



### Plug and play

Plug and play for easy networking.



### Wire Speed Forwarding

The switch features wire speed forwarding of all ports.

# Specifications


Model	G1016G
<b>Hardware Specifications</b>	
Network Standards	IEEE802.3, IEEE802.3u, IEEE802.3ab, IEEE802.3x
MTBF	50,000 hours
LED Indicators	One Link/Act LED indicator for each port One Power LED indicator for each device
Ports	16* 10/100/1000 Base-T Ethernet ports
Lightning Protection	≥6KV
Switching Mode	Store-and-forward
Switching Capacity	32Gbps
Forwarding Rate	23.8 Mpps
MAC Address Table	8K
Buffer	4 Mb
Input Voltage	AC: 100–240V 50/60Hz
Dimensions (L × W × H)	440 mm x 120 mm x 44 mm
Power Consumption	<12W
Environment	Operating temperature: 0°C – 45°C Storage temperature: –40°C – 70°C Operating humidity: (10% – 90%)RH, non-condensing Storage humidity: (5% – 90%)RH, non-condensing

## Software Specifications

Jumbo Frame	15K
Certificates	FCC、CE、RoHS

## Relevant Info

- Cable
- Optical fiber





**IP-COM NETWORKS CO.,LTD.**

Tower E3, No.1001, Zhongshanyuan Road,  
Nanshan District, Shenzhen, China. 518052  
Service: [info@ip-com.com.cn](mailto:info@ip-com.com.cn)  
Inquiry: [marketing@ip-com.com.cn](mailto:marketing@ip-com.com.cn)  
Tel: +86-755-27653089