

Addressable Input-Output Module



- IP 65 Protection
- Transparent lid
- Easy mounting

SensoIRIS MIO22 IP65 is an programmable input-output module, designed for application in addressable fire alarm systems, supporting TTE communication protocol. The module is mounted in a separate plastic box suitable for wall mounting with IP65 protection and possible for outdoor installations. The module monitors 2 analogue input signals and controls 2 relay outputs. SensoIRIS MIO22 IP65 is powered by the fire alarm panel and can be controlled via the communication protocol.

Features

- IP 65 Protection
- 2 programmable monitored inputs
- 2 programmable relay outputs
- Build-in isolator
- Enclosure box
- PC material
- Transparent lid for module status reading
- More room for cables inside the box

Technical Specifications

Operating Voltage Range	16 - 32VDC
Consumption, stand-by mode	235µA@27VDC
Nom. current consumption	260µA@27VDC
Outputs, electrical characteristics (max.)	DC 30V/1A; AC 125V/0.5A
Current consumption with 1 LED on	3.5mA
Current consumption with 2 LEDs on	7mA
Wire Gauge for terminals	0.4mm ² - 2.0mm ²
Operating temperature	-35°C to +60°C
Relative humidity resistance	(93 ± 3)% @ 40°C

Last update: 02.2025