

Analogue-addressable Fire Alarm Sounder



- Number of tone types - 32
- Supported TTE communication protocol
- Strobe light

SensoIRIS WS is an analogue-addressable Wall Mount Sounder designed for installing in analogue-addressable fire alarm systems supporting TTE communication protocol. The device is powered on from the panel and can be controlled via the communication protocol. SensoIRIS WS is compatible with fire bases B124/B124-HP for ceiling/wall mounting and WSB IP65 for outdoor usage.

Features

- Number of tone types – 32
- High or low sound levels
- Up to 60 SensoIRIS WSST per loop (low sound level)
- Supported TTE communication protocol
- Compatible with standard fire bases B124/B124-HP
- SAN, transparent material
- Red color

Technical Specifications

Operating Voltage Range	16 - 32VDC (Nom. 27VDC)
Nominal consumption (stand-by)	< 500µA@27VDC
Consumption in quiescent state, with communication	< 290µA@27VDC
Consumption in alarm state, with communication	6.5mA
Output in alarm state at terminal RI (terminals 4/1)	7.5 mA (max)/ 7.5V
Wire Gauge for terminals	2.5mm
Operating temperature	-35°C to +50°C
Relative humidity resistance	(93 ± 3)% @ 40°C
Weight (including base)	~183g

Last update: 02/2025