



Products ▾

Assemble kit

 Superior StreetSiren Plus Fibra

More ▾

Tech specs

SUPERIOR

Superior StreetSiren Plus Fibra

Wired siren with advanced sabotage protection and an extended list of compliance certificates. For outdoor and indoor use.



Device compatibility

Check

Communication

Fibra communication technology

Proprietary wired communication technology to transmit commands, alarms, and events.

Key features:

- Two-way communication.
- Advanced anti-sabotage.
- Instant notifications.
- Remote control and configuration in Ajax apps.

Learn more 

Line connection

4-core cable

Connection

to any point of the Fibra line

The device can be installed behind a hub, detector, keypad, or siren.

Fibra line length

up to 2,000 m

When using the U/UTP cat.5 twisted pair cable.

Calculate the line length at the facility 

Encrypted communication

All stored and transmitted data are protected by block encryption featuring a dynamic key.

Key features

Alarm type

acoustic and light

A speaker and LED frame

Type of warning device

type Z

External.

Type of acoustic output

tone

Alarm volume

from 85 to 107 dB at a distance of 1 m

Adjusted by a PRO or user with admin rights in the Ajax app.

Alarm duration

from 3 s to 3 min

Adjusted by a PRO or user with admin rights in the Ajax app.

Alarm sound

3 types

NFA2P-compliant, VdS-compliant, and Regular.

LED indication

2 types

The user can choose between the **Corner backlight** and **Full-frame backlight** features. **Full-frame backlight** works only when the siren has sufficient battery power.

Alarm LED indication in NFA2P-compliant mode

flashlight color — red

flashlight frequency — 1 flash per second

Siren sound frequency

- 1,400–1,600 Hz in NFA2P-compliant mode
- 1,400–1,800 Hz in VdS-compliant mode
- 1,400–1,600 Hz in Regular mode

Events indication

- Alarms.
- Delays when entering/leaving.
- Security mode.
- Security mode changing.
- After-alarm indication.

Chime

The siren makes a special sound to notify that the opening detectors are triggered when the system is disarmed.

Learn more 

Recommendations

The siren is designed for indoor and outdoor use. Recommended installation height is 2.5 m or higher.

Sabotage protection

Tamper alarm

Notifications on attempts to open the siren's enclosure, detach the siren from the surface, or remove the siren from the mounting panel.

[Learn more](#) ➤

Protection against forgery

device authentication

Communication loss detection

after 36 s

Detection time depends on the Jeweller/Fibra settings.

[Learn more](#) ➤

Power supply

Siren's operating voltage range

8–28 V₌₌

The siren is powered by the control panel.

Siren's nominal operating voltage

24 V₌₌

Maximum siren's current consumption at nominal voltage

50 mA

Quiescent siren's current consumption at nominal voltage

2.9 mA

Peak siren's current consumption at nominal voltage

217 μ A

When the siren sounds at the **Very loud** volume level.

Average siren's current consumption at nominal voltage

217 μ A

When the siren sounds at the default volume level. Regardless of the arming mode.

Battery

LTO 2.4 V $\equiv$ rechargeable battery

Pre-installed.

Capacity of the battery

3,000 mAh

The system notifies when the siren battery has 20% of its nominal capacity.

Electric shock protection class

Class III

Enclosure

Dimensions

210 × 210 × 71 mm

Weight of the white device

1,059 g

Weight of the black device

1,038 g

Operating temperature range

from -25 °C to +60 °C

Operating humidity

up to 95% with no condensation

Protection class

IP54, IK08



Colors

Black



White



Complete set

Superior StreetSiren Plus Fibra

SmartBracket mounting panel

Installation kit

Quick start guide

Certification and compliance with standards



Superior StreetSiren Plus Fibra



Additional information

Compliance with standards

Learn more ➤

User manual

Learn more ➤

Warranty

24 months

Learn more ➤

Subscribe

Subscribe to our emails about secure life. No spam.


Subscribe

Request extra help

✉ support@ajax.systems

📍 @AjaxSystemsSupport_Bot

💬 Send a request



Rating 4.7

4,000,000

people worldwide under Ajax protection

💡 Suggest a feature



Products

Intrusion protection

Video surveillance

Fire and life safety

Comfort and automation

All products

Services

System integrations

Ajax Ready products

Fibra wired protocol

Ajax radio protocols

Software

For users

Ajax PRO: Tool for Engineers

Ajax Desktop

Ajax PRO Desktop

Ajax Translator PRO

Ajax Cloud Signaling

Scenarios



Available on
App Store



Available on
Google Play

Solutions

Support

[Customer stories](#)[Solutions by facility type](#)[Commercial fire detection and alarm system](#)[Upgrades and retrofits](#)[Why Ajax](#)[How it works](#)[Manuals and articles](#)[Compliance with standards](#)

Tools

[Ajax device compatibility](#)[Video storage calculator](#)[Video device calculator](#)[Battery life calculator](#)[Radio communication range calculator](#)[Switches and outlets configurator](#)[Fibra power supply calculator](#)[All web tools](#)

Connecting to CMS

[Intrusion alarm monitoring](#)[Video monitoring and visual alarm verification](#)[Audio alarm verification](#)

Company

[Blog](#)[About us](#)[Press page](#)[Events](#)[Career](#)[Ajax Next](#)[Students at CES 2026](#)[Reviews and feedback](#)

For partners

[For partners](#)[Ajax Academy](#)[Partner Portal](#)[🇷🇴 România](#) [Privacy policy](#) [Report a vulnerability](#) [GDPR White Paper](#) [NDAA Statement](#) [Cookie policy](#) [Anti-Spam Policy](#)[End user agreement](#) [Warranty](#)

© 2025 AJAX SYSTEMS CH. All rights reserved