

UTP Category 5E Cables

Content of Data Sheet			
Product model	CAB-LC2100A -ECA-IN		
Product specification	Cat5e 4×2×0.5mm CPR ECA		
Test Standard	ISO/IEC11801、TIA-568-C.2 Fluke Test 100m (channel)		
Conductor	Material	Solid-Bare Copper	
	AWG	24	
	Nom.O.D.(mm)	0.5±0.01 mm	
	DC resistance	≤95 Ω/km	
Insulation	Material	HDPE	
	Thickness	0.2 ±0.01 mm	
	Diameter	0.9 ±0.05 mm	
	Color	Blue/White- Blue	
		Orange/White-Orange	Brown/White-Brown
Sheath	Material	LSZH (CPR ECA)	
	External O.D.	5.1±0.3 mm	
	Color	Gray(RAL7046)	
	Tensile strength	>10 Mpa	
	Thickness	0.55±0.05 mm	
Surface Printing	Letter height	3.0±0.3 mm	
	Color	Black	
	Print error & Space	1±0.005 m	
Packing	Packing	Carton	
	Once packing dimension	350mm*216mm*350mm	
	Twice packing dimension	370mm*460mm*370mm	
	Twice packing	2 cases	

	quantity	
Packing length	305±1 m	
Rip-cord	Yes	
Ambient temperature	-20°C ~ 60°C	

Zhejiang Uniview Technologies Co., Ltd.

No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China

Email: overseasbusiness@uniview.com; globalsupport@uniview.com

<http://www.uniview.com>

©2023-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.

*Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.