22 Inches LED Monitor

MW3222-V2



Features


- True color display
- Resolution is up to at 1920*1080
- Wide view of field: 178° (H)/ 178° (V)
- Specific menu design, which is simple to operate
- Adaptively recognize signal
- VESA stand bracket
- Support multiply language


Specifications


Model	MW3222-V2
Panel	
Backlight	ELED
Panel Size	22"
Resolution	1920 × 1080
Color Support	16.7M
Brightness (cd/m²)	250
Contrast Ratio	3000:1
Response Time (ms)	20
Pixel Pitch (H × V) (mm)	0.24 × 0.24
Viewing Angle (H/V)	Horizontal 178°, Vertical 178°
Display Size (mm)	478.6 × 260.2
Refresh Rate	100 Hz

Operation Hour	24/7
Bezel Width	2.0mm (top/left/right), 22.0mm (bottom)
Color Gamut	72% NTSC
Surface Treatment	Haze 25%, 3H
LCD Technology/Panel Type	VA
Interface	
Video Input	1 × VGA (MAX: 1920 × 1080@60 Hz) and 1 × HDMI (MAX: 1920 × 1080@100 Hz)
Audio Input	1 × Audio In (3.5mm Mini-Jack)
Speaker	
Speaker	2 × 1.5W
VESA	
VESA (mm)	100 × 100
Wall-mounted Thread	4-M4 screw hole, 10 mm Deep Thread
OSD	
Multi-Language	12 (English, German, French, Spanish, Italian, Dutch, Chinese, Japanese, Korean, Russian, Portuguese, Turkish)
General	
Input Voltage	DC 12V, 2A
Typical Power Consumption (W)	＜24
Standby Power Consumption (W)	＜0.5
Product Dimensions (W × H × D) (mm)	493.1 × 290.8 × 50.5 (No Pedestal) 493.1 × 378.6 × 200.0 (With Pedestal)
Package Dimensions (W × H × D) (mm)	557 × 370 × 140
Weight (kg)	Net Weight:2.3 Gross Weight:3.4
Operating Temperature	0°C ~ 40 °C
Operating Humidity	10%~90% (No Condensation)
Storage Temperature	-10°C ~ 60°C
Storage Humidity	10%~90% (No Condensation)
Material	Plastic
Lifetime (h)	30000
Certifications	CE, FCC
Standard	1 × 1.5m HDMI cable, 1 × Adapter, 1 × Pedestal, 1 × Quick Guide
MTBF (h)	50000


Dimensions


50.5
15.5
493.1
2.0
2.0
290.8
378.6
22.0
200.0




99.8
196.5
100.0
4-M4*10mm
100.0

Interface



Ordering Info

Product Model	Description
MW3222-V2	22 Inches LED Monitor

Unlimited New View

Zhejiang Uniview Technologies Co., Ltd.

http://www.uniview.com

overseasbusiness@uniview.com; globalsupport@uniview.com

No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China

©2023-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.

Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.