



UTP Category 5E Cables

Content of Data Sheet						
Product model	CAB-LC2100B-E-IN					
Product specification	HSYV-5e 4×2×0.45					
Test Standard	ISO/IEC11801 、TIA-568-C.2、IEC61156-6					
Conductor	Material	Solid-Bare Copper				
	Nom.O.D.(mm)	0.45±0.005 mm				
	DC resistance	≤115 Ω/km				
Insulation	Material	HDPE				
	Thickness	0.17±0.01 mm				
	Diameter	0.81±0.05 mm				
	Color	Blue/White- Blue			Green/White-Green	
		Orange /White-Orange			Brown/White-Brown	
Pitch	Offset pitch	≤25 mm				
	Cable pitch	≤140 mm				
Sheath	Material	PVC(complies RoHS/REACH)				
	External O.D.	4.7±0.3 mm				
	Color	Gray(RAL7046)				
	Tensile strength	>13.5 Mpa				
	Thickness	0.55±0.05 mm				
Surface Printing	Letter height	3.0±0.3 mm				
	Color	Black				
	Print error & Space	1±0.005 m				
	Case number	Yes				
Packing	Packing	Carton				



	Once packing dimension	340mm*220mm*340mm
	Twice packing dimension	360mm*470mm*360mm
	Twice packing quantity	2 cases
Packing length	305±1 m	
Rip-cord	Yes	
Ambient temperature	-20°C ~ 60°C	

Zhejiang Uniview Technologies Co.,Ltd.

Building No.10, Wanlun Science Park, Jiangling Road 88, Binjiang District, Hangzhou, Zhejiang, China

Email: overseasbusiness@uniview.com; globalsupport@uniview.com

<http://www.uniview.com>

©2011-2018 Zhejiang Uniview Technologies Co.,Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.