

DS-PDC15-EG2-WE

DS-PDC15-EG2-WE is a two-way wireless detector featuring a solid curtain coverage up to 15m length by 3.6m height, it suitable for perimeter protection by setting up detection "curtain" walls or windows

- Long range with narrow angle detection
- Fully remote configurable through App
- Multiple enrollment method and easy installation design
- Easy replaceable battery with PCB protected
- Frequency hopping against jamming for reliable transmission



Specification

Detection Performance			
Detection Method	Passive Infrared		
Detection Range	15 m		
Detection Angle	6.3°		
Detection Zones	18		
Detectable Speed	0.3 ~ 2 m/s		
Pet Immunity	None		
White Light Filter	6500lux		
Digital Temperature Compensation	Support		
Creep Zone Protection	Support		
Feature			
Digital Processing	Support		
Sealed Optics	Support		
Tamper Protection	Front,Rear		
Environment Temperature	Support		
Indicator	Support		
Signal Strength Indicator	Support		
Interface			
Power Switch	Power Up Enrolling		
LED Indicator	Blue(Alarm)		
Transmission			
Transmission Technology	Tri-X Wireless		
Transmission Method	Two-Way RF Wireless		
Transmission Frequency	868 MHz		
Transmission Security	AES-128 Encryption		
Transmission Range(Free Space)	1.6Km		
Frequency Hopping	Support		
Enrolling Method	Power up, Remote ID, QR Code		
Electrical Characteristics			
Standard Battery Life	5 years in work status (being triggered 20 times per day)		
Power Supply	Battery Powered		
Battery Type	CR123A × 1		
Typical Voltage	3 V		
General			
Operation Temperature	-10 °C to 55 °C (14 °F to 131 °F)		
Storage Temperature	-20 °C to 60 °C (-4 °F to 140 °F)		
Operation Humidity	10% to 90%		
Dimension(W × H × D)	65.5 mm × 103 mm × 48.5 mm		
Weight	128 g		
Mounting Height	2.4 to 3.6 m		
Mounting Method	Wall		



Application Scenario	Indoor
Bracket	Optional Wall & Ceiling Accessory

Available Model

DS-PDC15-EG2-WE

Accessory

Optional

DS-PDP-IN-CR123A	DS-PDB-IN-Ceiling bracket	DS-PDB-IN-Wall bracket
Indoor Detector	Internal ceiling mounted	Internal wall mounted
Battery	bracket	bracket
Lithium Battery Likhno, + CR123A 3.0V - CR123A 3.0V - Con Not Recharge!		2





Headquarters No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 www.hikvision.com

Follow us on social media to get the latest product and solution information.





HikvisionHQ



HikvisionHQ







hikvisionhq