

10 W 8" ceiling loudspeaker EN 54, metal



Part-No.: 582402

Ceiling mount loudspeaker in plastic coated metal work with high efficiency and moisture proof broadband loudspeaker chassis, certified as per EN 54-24.

DL 10-200/T-EN 54 (200 mm Chassis) has maximum power of 20 W and can be adjusted to 6 W, 10 W or 1.5 W if required. Spring clamps with cropped leg spring, with high clamping force, and short tension distance enables a quick and easy mounting. A smart inner ring prevents the grille from collapsing even under heavy load due to environmental influences. For additional protection, this EN 54-24 ceiling mount loudspeaker is assembled with ceramic clamp and thermal fuse as well as equipped with a fire dome. It has PG16-cable outlet and a blind cover. The fire dome prevents the suction effect of the chimney at the suspended ceiling in case of fire, after possible burning of the loudspeaker membrane.

Rated Power	10 W
Sensitivity EN 54-24, 1 W / 1 m	93,9 dB
Sensitivity EN 54-24, max 1 m	103,4 dB
Transmission range	243 Hz ... 19700 Hz
Ambient temperature	-20 °C ... 80 °C
Color	white, similar to RAL 9010
Weight	approx. 2,1 kg
Cut-out size	(Ø min.) 238 mm
Dimensions	Ø: 268 mm D: 217 mm



Delivery time on request