

6 W 5" ceiling loudspeaker EN 54.SAFE, metal



Part-No. 582407.SAFE

Approval as per EN 54-24, 1438/CPD/0233

With its flat form, the type DL-E 06-130/T-EN 54.SAFE is optically a good fit for the ceilings for which they were designed. The SAFE versions are equipped with a premounted ceramic terminal and a thermal fuse. The 5" broadband loudspeaker chassis, which is impregnated against humidity, distinguishes itself by way of its high degree of effectiveness. Typically, the 6 W, 3 W, or 1.5 W power setting can be selected. The spring latch (2 pieces) guarantees uncomplicated and quick mounting onto the ceiling. In the standard version, a protective cover made out of a synthetic material is mounted to the back side of the loudspeaker, but a fire dome certified according to the EN 54 Part 24 standard is optionally available as well. This is also necessary in order to mount this SAFE-type also in projects which require compliance with BS 5839-8.

Ambient temperature	-10 °C ... 55 °C
Rated Power	6 W
Transformer power taps	6/3/1.5 W
Color	white, similar to RAL 9016
Weight	approx. 0.75 kg
Dimensions	Ø: 181.5 mm D: 59 mm

Accessories:

Optional:
582407.FD Fire dome (FE 130.1)