

Linea LEN-60 EN 54-24, black

Part-No.: 582652.B



Passive 100 V loudspeaker, with weatherproof aluminium housing, designed for use with voice alarm systems - certified according to EN 54-24, Type B, equipped with two high-quality 4" drivers with treated cones for optimum efficiency in speech and voice alarms.

SPL Pmax / 1 m	112 dB
Sensitivity EN 54-24, 1 W / 4 m_comp	83 dB
Dispersion angle	130° (H) x 25° (V) nominal; 360° (H) x 90° (V) @500 Hz; 190° (H) x 40° (V) @ 1000 Hz; 120° (H) x 25° (V) @ 2000 Hz; 95° (H) x 13° (V) @ 4000 Hz
Housing	weatherproof aluminium housing, powder coated, steel bracings
Color	black, similar to RAL 9005, powder-coated
Weight	approx. 7,5 kg
Dimensions	W: 130 mm H: 640 mm D: 120 mm

Features:

- EN 54-24 certified, 100 V loudspeaker for use with voice alarm systems
- suitable for both indoor and outdoor use
- exceptionally even sound dispersion
- SIDE LOBE FREE – passive realization
- equipped with high performance speakers
- excellent speech intelligibility and sound quality
- a long reach
- weatherproof without requiring additional protection (protection class IP54 in accordance with IEC 529 / EN 60529)
- ball impact resistant front grille made from galvanised sheet steel

Accessories:

582614.B Wall mount WLX-100, black