

Tech specs

BASELINE

NVR (8-ch)

Network video recorder for 8 channels



Compatibility

Control panels

Hub >

Hub Plus >



[Hub 2 \(2G\) >](#)

[Hub 2 \(4G\) >](#)

[Hub 2 Plus >](#)

[Hub Hybrid \(2G\) >](#)

[Hub Hybrid \(4G\) >](#)

[Differences between hubs >](#)

Videostream

NVR models

8-channel

With up to 4K resolution (25/30 FPS).

IP cameras

- ONVIF (Profile S/T)
- RTSP

[Learn more >](#)

Storage

hard drive with a capacity of up to 16 TB (SATA connectivity, 3.5" size)

HDD not included.

Decoding formats

H.265

H.264

Bandwidth

up to 100 Mbps

NVR

[Where to buy](#)

The device operating voltage is 110–240 V~.

NVR is designed for indoor installation only.

Communication channels

Ethernet

up to 100 Mbps

Bluetooth

BLE frequency band: 2.400–2.4835 GHz

To set up an Ethernet connection.

Radio signal power

2.5 mW (100 mW limit)

Key features

Motion detection

NVR has built-in software to detect the motion in the frame. Possible to switch between image analysis by NVR or camera algorithms.

In-app video management system

- Videowall that combines images from all connected cameras.
- Event filters.
- Timeline with smooth preview.

Visual verification of Ajax alarms

NVR allows setting up a scenario in which Ajax detectors trigger specific cameras to start recording. This results straight in mobile and desktop (monitoring) apps.

Privacy

Access rights distribution for users in mobile apps and for monitoring operators in PRO Desktop.

Power supply

Main

110–240 V~, 50/60 Hz, 0.6 A

Up to 24 W of mains power consumption.

Backup

CR2032 battery, 3 V

Only to power the system clock.

Sabotage protection

Tamper alarm

Notifications about attempts to detach the device from the surface or remove it from the mounting panel.

[Learn more](#) >

Enclosure


Dimensions

251 × 251 × 51 mm

Weight

700 g

Without a hard drive.



Operating temperature range

from 0°C to +40°C

Operating humidity

up to 75%

Protection class

IP20



51 mm

Colours

Black



White



Complete set

NVR

SmartBracket mounting panel

Power cable

Ethernet cable

Installation kit

Quick start guide

Additional information

Compliance with standards

[Learn more >](#)

User manual

[Learn more >](#)

Warranty

24 months

[Learn more >](#)

Subscribe

Subscribe to our emails about secure life. No spam.

[Subscribe](#)

Request extra help

✉ support@ajax.systems



Products

- Superior
- Fibra
- Intrusion protection
- Video surveillance
- Fire detection
- Water leak prevention
- Comfort & Productivity

Solutions



- Why Ajax
- How it works
- Scenarios
- Customer stories
- Ajax Ready products
- Reviews and feedback

Company

- Blog
- About us
- Press page
- Events
- Career

Software

- For users
- PRO Desktop
- Ajax Translator
- Scenarios



Support

- Manuals and articles
- Compliance with standards

Tools

- Battery life calculator
- Radio communication range calculator
- Fibra power supply calculator
- Light switches configurator
- Ajax devices compatibility

For partners

- Bussiness with Ajax
- Events
- Brandbook
- Ajax SIM
- Enterprise API
- CMS integration

 [România](#) [Privacy policy](#) [GDPR White Paper](#) [NDAA Statement](#) [Cookie policy](#) [Anti-Spam Policy](#) [End user agreement](#)

[Warranty](#)

© 2023 AJAX SYSTEMS CH. All rights reserved